

## tesa® 62852

### Double-sided PE foam tape

tesa® 62852 is a double-sided tape consisting of a PE foam backing and a pure acrylic adhesive.

tesa® 62852 features especially:

- High ultimate adhesive strength for a secure bonding performance
- Conformable foam backing to compensate design tolerances or uneven surfaces
- Excellent temperature resistance performance
- Excellent converting properties

### Main Application

- Permanent mounting of emblems and letters; e.g. single letters for classification of car model or engine data

### Technical Data

▪ Backing material	PE foam	▪ Tensile strength	8 N/cm
▪ Color	black	▪ Type of liner	glassine
▪ Total thickness	510 µm	▪ Colour of liner	brown
▪ Type of adhesive	pure acrylic	▪ Thickness of liner	71 µm
▪ Elongation at break	400 %	▪ Weight of liner	80 g/m <sup>2</sup>

### Adhesion to

▪ Steel (initial)	9.5 N/cm	▪ Steel (after 14 days)	20.0 N/cm
▪ ABS (initial)	6.0 N/cm	▪ ABS (after 14 days)	13.0 N/cm
▪ PE (initial)	1.5 N/cm	▪ PE (after 14 days)	1.5 N/cm

### Properties

▪ Temperature resistance short term	100 °C	▪ Static shear resistance at 40°C	● ● ● ●
▪ Temperature resistance long term	90 °C	▪ Static shear resistance at 70°C	● ● ● ●
▪ Static shear resistance at 23°C	● ● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=62852>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.