

# tesa® Powerstrips Waterproof Hook Metal



BNR 59707, 59765

## Product Features

- Easy to mount without drilling, screws or nails
- Strong hold of up to 2 kg
- Removable without a trace due to the Powerstrips® Waterproof technology
- Made from stainless steel
- Usable on tiles, glass, etc. in humid rooms or directly in the shower\*
- Especially developed for wet areas (e.g. shower, bathtub etc.)
- Hook reusable with tesa Powerstrips Waterproof

\*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

## Product Description

The self-adhesive tesa Powerstrips Waterproof Hook Metal is a removable bathroom hook combining modern design with the strength to hold weights of up to 2 kg.

## Application Fields

- How to apply - step-by-step:
1. Clean the surface with alcohol or silicone-free glass cleaner
  2. Take the included waterproof primer tissue and wipe over the surface for bonding preparation - wait for 10 seconds minimum
  3. Apply the Powerstrip Waterproof Large strip on the surface - press for 5 seconds minimum
  4. Disengage the base plate of the hook and stick it onto the strip - press for 5 seconds minimum
  5. Let the hook slide down on the base plate until it is locked

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                       |             |                    |                  |
|-----------------------|-------------|--------------------|------------------|
| • Hook shape          | Rectangular | • Type of adhesive | synthetic rubber |
| • Holding power up to | 2 Kg        |                    |                  |

# tesa<sup>®</sup> Powerstrips Waterproof Hook Metal

## Properties/Performance Values

• Applicationfield	Bathroom, Kitchen	• Reusable	yes
• Chemical resistance	no	• Oil and grease resistance	no
• Reusable with	Powerstrips Waterproof Large	• Hazard material	yes
• Residue free removal	yes	• UV resistant	no
• Ozone resistance	no	• Material	Stainless steel
• Solvent free	yes	• Temperature resistance	yes
• Application temperature	from 15° up to 35° °C	• Humidity resistance	yes

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=59707>