

tesa[®] ALUXX Corner Shower Caddy, Self-Adhesive, Chromed Aluminium



Product Information

BNR 40203

Product Description

Attaching the self-adhesive tesa[®] Aluxx corner shower caddy to a wall is a breeze, and no drilling is needed. That way, surfaces stay untouched. At any time, the basket can be taken off without a trace and reused elsewhere with a new adapter BK43-2. The glossy metal and the minimalistic design are beautiful.

Product Features

- Corner shower caddy with floor panel, with tesa® Power.Kit technology (all-in-one adhesive mounting solution)
- · High gloss chrome-plated aluminum, round style, circular wall plates
- Reliable hold, waterproof, guaranteed stainless
- · Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- · Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Quick removal without a trace and can be relocated with new adapter BK43-2
- Drilling not involved, effortless mounting
- Product dimensions: 92mm x 250mm x 125mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

٠	Type of adhesive	Silane modified	•	Hook shape	Round
		polymer			
٠	Holding power up to	5 Kg			

Properties/Performance Values

 Applicationfield Area of use Batteries included Batteries required Chemical Resistance Curing time Design series Hazard material 	Bathroom Indoor no no 12 hour(s) tesa® ALUXX yes	 Material Residue-free removability Reusable Reusable with Shape of wall piece Solvent free Suitable surfaces 	Chromed Aluminium yes yes Adapter BK43-2 Round yes Glazed Tiles, Marble, Glass, Metal, Stone,
 Hazard material Humidity resistance 	yes yes	UV resistantWaterproof	Concrete, Even wood, Most plastics yes yes

Waterproof



tesa® ALUXX Corner Shower Caddy, Self-Adhesive, Chromed Aluminium

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 29/02/24 – en-US