

tesa® ELEGAANT Spare Roll Holder, Self-Adhesive, Chromed Metal

Product Information

BNR 40444

Product Description

The smoothed square design gives the dazzling tesa® Elegaant spare roll holder a particularly striking look. For application, drilling is not needed since an adhesive solution is used instead, avoiding any damage to walls or tiles. The holder can be removed cleanly and remounted elsewhere with a new adapter BK20.

Product Features

- Robust spare roll holder, including the tesa® Power.Kit technology (the all-in-one adhesive mounting solution)
- · Elegant design, smoothed angular style, high gloss chrome-plated metal, smoothed square wall plate
- · Reliable hold, waterproof, guaranteed stainless
- · Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- · Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Can be taken off without a trace or surface damage. Can be re-attached with adapter BK20
- · Clean, simple mounting without drilling
- Product dimensions: 50mm x 50mm x 128mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	Silane modified	•	Hook shape	Rounded square
		polymer			
•	Holding power up to	6 Kg			

Properties/Performance Values

•	Applicationfield	Bathroom	•	Material	Chromed metal
•	Area of use	Indoor	•	Residue-free removability	yes
•	Batteries included	no	•	Reusable	yes
•	Batteries required	no	•	Reusable with	Adapter BK20
•	Chemical Resistance	no	•	Shape of wall piece	Rounded edges
•	Curing time	12 hour(s)	•	Solvent free	yes
•	Design series	tesa® ELEGAANT	•	Suitable surfaces	Glazed Tiles, Marble,
•	Hazard material	yes			Glass, Metal, Stone,
•	Lid	Without lid			Concrete, Even wood,
					Most plastics
				LIV/ recictant	1100

UV resistantWaterproofyes



tesa® ELEGAANT Spare Roll Holder, Self-Adhesive, Chromed Metal

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

