

# tesa® Professional Spray Glue Permanent



### **Product Information**

BNR 60020, 60021

## **Product Description**

tesa® Spray Glue Permanent is a spray adhesive for large surfaces. It offers extra stong bonding for typical household materials such as paper or cardboard.

#### Caratteristiche

- · For clean, economical, secure and fast bonding of large areas
- · Suitable for light and medium-weight materials with slightly uneven surfaces
- · Finely and evenly dispersion of glue
- Fast drying
- Resistant to damp and temperature from -20°C up to +60°C
- Suitable for Styrofoam®
- · Free from silicone

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

Senza silicone yes

## Proprietà/Valori di prestazione

<ul> <li>Adatto ai bambini di 3 anni</li> </ul>	no	<ul> <li>Resistente ai raggi UV</li> </ul>	yes
<ul> <li>Adesività</li> </ul>	High adhesion	<ul> <li>Resistente all'acqua</li> </ul>	yes
Batterie incluse	no	<ul> <li>Resistenza ad agenti chimici</li> </ul>	yes
<ul> <li>Batterie richieste</li> </ul>	no	<ul> <li>Resistenza all'umidità</li> </ul>	yes
<ul> <li>Campo di applicazione</li> </ul>	A casa, Ufficio	<ul> <li>Resistenza alla temperatura</li> </ul>	yes
<ul> <li>Compostabile</li> </ul>	no	<ul> <li>Resistenza massima alla</li> </ul>	60 °C
<ul> <li>Distanza raccomandata per lo</li> </ul>	20 mm	temperatura	
spray		<ul> <li>Resistenza min. alle</li> </ul>	-20 °C
<ul> <li>Imballaggio ecologico</li> </ul>	no	temperature	
<ul> <li>Lavabile</li> </ul>	no	<ul> <li>Rimozione senza residui</li> </ul>	no
<ul> <li>Materiale pericoloso</li> </ul>	yes	<ul> <li>Riutilizzabile</li> </ul>	no
<ul> <li>Privo di solventi</li> </ul>	no	<ul> <li>Superfici adatte</li> </ul>	Even wood, Stone,
			Brick, Acrylic glass



# tesa® Professional Spray Glue Permanent

**Product Information** 

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

