

tesapack® Eco & Strong



57 um

Product Information

BNR 58154, 58156, 58226, 58155, 58153, 58227

Product Description

tesapack® eco & strong is a more sustainable packaging tape made from 100% recycled pastic. It is free from PVC and solvents

Caratteristiche

- Strong PP backing made from 100% recycled plastic
- Core made from 100% recycled cardboard
- · Label made from paper
- Solvent-free adhesive with high UV-resistance
- · High sealing security
- · Even, low noise unwinding
- Suitable for use with all available tesapack® hand dispensers
- The recycled content has been approved by the independent certification organisation DIN CERTCO belonging to the TÜV Rheinland (German technical control board).

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Spessore totale

Product Construction

Supporto

			- · · · · · ·					
Massa adesiva	water-based acrylic							
Proprietà/Valori di prestazione								
Allungamento a rottura	00 %	Drivo di colventi	1400					

BOPP

•	Allungamento a rottura	80 %	•	Privo di solventi	yes
•	Resistenza alla trazione	40 N/cm	•	Resistente agli strappi	yes
•	Adesività	High adhesion	•	Resistenza all'invecchiamento	yes
•	Batterie incluse	no		(UV)	
•	Batterie richieste	no	•	Resistenza all'umidità	no
•	Campo di applicazione	A casa, Ufficio	•	Rimozione senza residui	no
•	Controllo della trazione	_NULL	•	Riutilizzabile	no
•	Forza di srotolamento n/cm	3.7 N/cm	•	Scrivibile	no
•	Lama seghettata	_NULL	•	Servizio pezzi di ricambio	no
•	Larghezza max. del rotolo	50 mm	•	Strappabile a mano	no
•	Lunghezza massima del rotolo	66 m	•	Superfici adatte	Cartone
•	Materiale	PP (Polipropilene)	•	Svolgmento silenzioso	yes
			•	Tensione	80 %



tesapack® Eco & Strong

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

