



tesafilm® double-sided

Product Information



BNR 57911, 57954, 57910, 57912

Product Description

tesafilm® double-sided is a special-purpose self-adhesive tape especially designed to stick paper, cardboard and photographic prints.

Caratteristiche

- Double-sided adhesive
- Transparent
- Good adhesion
- High age-resistance
- Easy unwinding
- PP foil

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------|---------------------|-------------------|-------|
| • Supporto | BOPP | • Spessore totale | 75 µm |
| • Massa adesiva | water-based acrylic | | |

Proprietà/Valori di prestazione

- | | | | |
|----------------------------------|--------------------|--------------------------------------|---------|
| • Resistenza alla trazione | 58 N/cm | • Materiale pericoloso | no |
| • Adatto per destrorsi e mancini | _NULL | • Privo di solventi | no |
| • Adesività | High adhesion | • Resistente agli strappi | no |
| • Batterie incluse | no | • Resistenza all'invecchiamento (UV) | yes |
| • Batterie richieste | no | • Rimozione senza residui | no |
| • Campo di applicazione | A casa, Ufficio | • Riutilizzabile | no |
| • Imballaggio ecologico | _NULL | • Scrivibile | no |
| • Invisibile sulle fotocopie | no | • Strappabile a mano | no |
| • Lama seghettata | _NULL | • Superfici adatte | Cartone |
| • Larghezza max. del rotolo | 19 mm | • Svolgimento silenzioso | yes |
| • Lunghezza massima del rotolo | 33 m | • Tensione | 80 % |
| • Materiale | PP (Polipropilene) | • Trasparenza | medium |



tesafilm[®] double-sided

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>