



# tesa<sup>®</sup> Masking Tape Professional Sensitive

## Product Information

BNR 56260, 56261, 56267, 56256

## Product Description

tesa<sup>®</sup> Masking Tape Professional Sensitive is an extra thin paper contour liner that allows safe removal even on sensitive surfaces such as wallpaper.

## Caratteristiche

- For sensitive surfaces and wallpapers
- Residue-free removal for up to 14 days
- Solvent-free
- For pretentious painting jobs which have to be exact and precise
- Suitable for all paints

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                 |            |                   |       |
|-----------------|------------|-------------------|-------|
| • Supporto      | flat paper | • Spessore totale | 80 µm |
| • Massa adesiva | acrylic    |                   |       |

## Proprietà/Valori di prestazione

- |                            |         |  |                       |
|----------------------------|---------|--|-----------------------|
| • Resistenza alla trazione | 32 N/cm | • Batterie richieste                     | no                    |
| • Area d'uso               | Indoor  | • Campo di applicazione                  | Professionale, A casa |
| • Batterie incluse         | no      | • Rimovibile senza residui dopo...giorni | 14 days               |



# tesa<sup>®</sup> Masking Tape Professional Sensitive

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>