

# tesa® LOXX Hook, Self-Adhesive, Chromed Metal

**Product Information** 

## BNR 40276

## **Product Description**

It's a breeze to attach the self-adhesive tesa<sup>®</sup> Loxx bath hook to a wall without drilling and without damage to walls or tiles. The bath hook can also easily be removed at your convenience, without a trace. Reuse only requires a new adapter BK22. The hook's spirited, rounded design is a pleasure to see.

## Caratteristiche

- Bath hook, with tesa® Power.Kit technology (all-in-one adhesive mounting solution)
- High gloss chrome-plated metal, round style, circular wall plate, cheerful design
- Reliable hold, waterproof, guaranteed stainless
- Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Fast to remove without a trace, reusable with adapter BK22
- Easy to apply without drilling
- Product dimensions: 42mm x 42mm x 50mm

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## **Product Construction**

• Mas	isa adesiva	Silane modified	•	Tenuta fino a	6 Kg
		polymer			
<ul> <li>Forr</li> </ul>	na gancio	Round			

## Proprietà/Valori di prestazione

•	Area d'uso	Indoor	Resistente all'acqua yes	
•	Batterie incluse	no	Resistenza ad agenti chimici no	
•	Batterie richieste	no	Resistenza all'umidità yes	
•	Campo di applicazione	Bagno	Rimozione senza residui     yes	
•	Design series	tesa® LOXX	Riutilizzabile yes	
•	Materiale	Metallo cromato	Riutilizzabile con     Adapter BK22	)
•	Number of hooks	Singolo, Doppio	Shape of wall piece Rotonda	
•	Privo di solventi	yes	Superfici adatte piastrelle sma	ltate,
•	Resistente ai raggi UV	yes	Vetro	
			Tempo di polimerizzazione 12 hour(s)	



# tesa® LOXX Hook, Self-Adhesive, Chromed Metal

**Product Information** 

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 15/03/24 – it-CH