



# tesa<sup>®</sup> BASIC Masking tape

## Product Information

BNR 58594, 58598, 58591, 58592, 58599, 58593, 58596

## Product Description

Saturated semi-crepe paper masking tape coated with natural rubber adhesive. Suitable for general masking applications.

## Product Features

- General masking
- Residue-free removal
- Solvent and thinner resistant
- Easy tear
- Suitable for water and solvent based paints

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- Backing Paper

## Properties/Performance Values

- |                         |        |                                   |        |
|-------------------------|--------|-----------------------------------|--------|
| • Applicationfield      | Home   | • Residue-free removability       | yes    |
| • Area of use           | Indoor | • Residue-free removable after... | 3 days |
| • Batteries included    | no     | days                              |        |
| • Batteries required    | no     | • Reusable                        | no     |
| • Ecofriendly packaging | yes    | • Spare part service              | no     |
| • Hand tearability      | yes    | • Tear resistance                 | yes    |
| • Hazard material       | no     | • UV resistant                    | yes    |
|                         |        | • Writable                        | yes    |



# tesa<sup>®</sup> BASIC Masking tape

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>