



tesa® Duct Tape >60% Recycled Plastic

Product Information

BNR 56499, 56498, 04615

Product Description

Consciously sourced without compromise: tesa® Duct Tape's backing is made from > 60% post-consumer recycled (PCR) material, making it a reliable all-rounder tape for everyday.

Sustainable Aspects

By incorporating > 60% post-consumer recycled (PCR) material into its backing component, tesa® Duct Tape offers an increased recycled material content without compromising performance.

Product Features

- Contributing to sustainability: The backing is made from > 60% post-consumer recycled material (PCR)
- Strong hold: The repairing tape sticks firmly and reliably even to very rough surfaces
- Easy to use: The tape can be conveniently torn by hand, making it ready for use
- Weather-ready: The waterproof, weather-resistant tape offers a strong hold both indoors and outdoors
- Versatile all-rounder: Ideal for DIY projects, fixing, sealing or repairs
- Improved Packaging: Product packaging contains of 50% post-industrial recycled (PIR) content
- Scope of delivery: 1 x roll of tesa® Duct Tape, Multi-Purpose Duct Tape

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|---|--------------------|--------------------|------------------|
| • Backing | PE laminated cloth | • Type of adhesive | synthetic rubber |
| • Post-consumer recycled content of backing | 63 % | • Total thickness | 175 µm |

Properties/Performance Values

- | | | | |
|--------------------------------|-------------------|-----------------------------|---|
| • Elongation at break | 18 % | • Ecofriendly packaging | yes |
| • Tensile strength | 41.5 N/cm | • Hand tearability | good |
| • Abrasion resistance | good | • Humidity resistance | yes |
| • Adhesive strength | Standard adhesion | • Residue-free removability | no |
| • Ageing resistance (UV) | medium | • Solvent free | yes |
| • Application temperature from | 5 °C | • Suitable surfaces | Even wood, Tiles,
Most plastics, Glass,
Metal |
| • Application temperature to | 60 °C | | |
| • Area of use | In- and Outdoor | • Tear resistance | yes |
| • Chemical Resistance | medium | • Waterproof | yes |

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>



tesa[®] Duct Tape >60% Recycled Plastic

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>