

tesa® 4329 PV1



Product Information

Finely creped paper mask tape

Product Description

tesa® 4329 is a slightly creped, easy-to-use paper mask tape that is suited to a wide range of uses. It is often used by craftsmen for carrying out varnish work, in order to safely and reliably protect individual car or motorbike components. This mask tape is watertight, resistant to temperatures of up to 70 °C and bonds with both varnishes and fillers. Thanks to the adhesive strength of its natural rubber mass, this mask tape ensures a good adhesion on various surfaces and enables precise edges during varnish work.

Product Features

- Masking
- Lacquering work
- Good flexibility for curves
- Can be used on painted metal, rubber, glass and chrome parts

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|--|--------|
| • Backing | slightly-creped paper | • Total sustainable product excl. liners by weight (acc. EN 16785) | 57 % |
| • Type of adhesive | natural rubber | • Total thickness | 125 µm |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------------------|-----------|
| • Elongation at break | 10 % | • Hand tearability | very good |
| • Tensile strength | 33 N/cm | • Temperature resistance (60 min) | 80 °C |
| • Easy to remove | yes | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 2.8 N/cm |
|---------|----------|

tesa® 4329 PV1

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4329>