

tesa[®] Professional 60021 Spray Glue Permanent

Product Information

Spray glue for many kinds of applications in the crafts

Product Description

tesa[®] Spray Glue PERMANENT 60020 is a very versatile glue for permanently bonding materials such as paper, cardboard, felt, fabric, film, wood, leather, polystyrene and many different plastics.

- For clean, cost efficient, secure and fast bonding of large areas
- Suitable for light to medium-weight material with smooth to uneven surfaces
- The glue is dispersed finely and evenly
- Fast-drying and resistant against damp and mechanical and thermal stresses
- Suitable for gluing Styrofoam
- Free from silicone and chlorinated solvents

Application Fields

- Permanent large area gluing
- Bonding materials such as paper, cardboard, felt, fabric, film, wood, leather, many plastics
- Particularly suited for uneven surfaces
- Marking of pallets
- Attaching circuit diagrams and labels
- Gluing posters and templates
- Suitable for gluing Styrofoam®
- Short-term repairs at events

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Silicone free

yes



tesa[®] Professional 60021 Spray Glue Permanent

Product Information

Properties/Performance Values

| Adhesive strength | High adhesion |
|---|---------------|
| Applicationfield | Office, Home |
| Batteries included | no |
| Batteries required | no |
| Chemical Resistance | yes |
| Compostable | no |
| Ecofriendly packaging | no |
| Hazard material | yes |
| Humidity resistance | yes |
| Recommended distance of | 30 cm |
| spraying | |
| Residue-free removability | no |
| | |

| ٠ | Reusable | no |
|---|---|---|
| ٠ | Solvent free | no |
| • | Suitable for children of 3 years of age | no |
| • | Suitable surfaces | Even wood, Stone, Brick, Acrylic glass |
| • | Temperature resistance | yes |
| • | Temperature resistance max. | 60 °C |
| ٠ | Temperature resistance min. | -20 °C |
| ٠ | UV resistant | yes |
| ٠ | Washable | no |
| ٠ | Waterproof | yes |
| | | |

Additional Information

tesa®

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



²age 2 of 2 – as of 02/04/24 – en-NG