



tesa® Professional 4169 Permanent Marking Tape Premium

Product Information

Premium floor marking tape

Product Description

tesa® 4169 is an extremely robust high-performance adhesive tape for permanent floor markings. The abrasion-resistant, robust and resilient floor-marking tape comprises a soft PVC substrate with an acrylate adhesive mass. It can also be used on sensitive or rough surfaces and, thanks to the high degree of flexibility in the substrate, is also suitable for adhesion to corners. tesa® 4169 is available in black, green, white, blue, red, yellow and yellow/black; the colour combinations correspond to legally prescribed safety guidelines. Depending on its colour, the floor-marking tape can be explicitly used as a warning tape.

Application Fields

- Indoor and outdoor applications
- Permanent, high-traffic floor markings
- Marking of working areas in workshops
- Mark out courts in sports halls

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------|-------------------|--------|
| • Backing | soft PVC | • Total thickness | 180 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------|------|
| • Elongation at break | 200 % | • Hand tearability | good |
| • Tensile strength | 30 N/cm | • Humidity resistance | good |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 1.8 N/cm |
|---------|----------|



tesa® Professional 4169 Permanent Marking Tape Premium

Product Information

Additional Information

The plain colours of tesa® 4169 PV3 are according to the RAL colour scheme.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04169>