



tesa® 52664

Product Information



Plate mounting in flexographic printing, especially corrugated board postprint

Product Description

tesa® 52664 consists of a tear resistant flexible fabric backing, with a rubber adhesive system. The adhesive has a high coating weight making it well suited to mounting plates in flexographic printing applications, especially in corrugated board postprint. High adhesion and backing strength also ensure secure vertical storage of mounted plates.

tesa® 52664 can be removed easily without leaving adhesive residues.

Adhesive:

- High adhesion values for reliable application, even when stored vertically for longer periods
- High adhesion and shear also ensure that there is no edge lifting, even on longer print runs and at higher speeds

Backing

- Cloth backing for excellent, reliable bond, even when stored vertically.

Application Fields

tesa® 52664 is especially well suited to plate mounting in corrugated board postprint, due to its ideal adhesive characteristics and optimal backing properties.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-----------------|----------|
| • Backing | cloth | • Type of liner | glassine |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | |
|----------------------|-----|
| • Thickness category | 380 |
|----------------------|-----|



tesa[®] 52664

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=52664>