

# tesa<sup>®</sup> Softprint 52814 SEC

**Product Information** 

Plate mounting tape for photopolymer plates in flexographic printing

# **Product Description**

Double-Sided foam tape for Flexographic Printing

### Foam Properties

- Low thickness tolerance
- Long lasting, constant recovery characteristics

### Adhesive Properties

- Low tack surface characteristics
- Strong adhesion on both sides
- Solvent resistance

### Additional Properties

- Structured PP liner
- Logo colour indicates foam hardness

# **Application Fields**

Mounting of 1.14 mm (0.45") and 1.70 mm (0.067") thickness, PET backing, flexographic printing plates onto steel / alu / PU and glassine cylinders and sleeves.

# Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## **Product Construction**

<ul><li>Backing</li><li>Type of adhesive</li></ul>			Type of liner Total thickness	PP 430 μm
Properties/Performance Values				
<ul><li>Color of logo</li><li>Hardness</li></ul>	green hard	•	Thickness category	380





# tesa® Softprint 52814 SEC

**Product Information** 

# Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.