



tesa[®] 4101 PV2



Product Information

Adhesive film of cellulose hydrate for packaging

Product Description

tesa[®] 4101 PV 2 is based on a cellulose hydrate film coated with a rubber adhesive. The backing, which is composed of a sustainable material, is characterised by a high rigidity and low electrostatic charging. For this reason long strips of the tape can be dispensed without any curling. The tape can easily be torn by hand.

Cellulose Hydrate film can be cleanly cut (separated) by an adjacent tesa[®] tear strip.

Application Fields

tesa[®] 4101 PV 2 is mainly used for general packaging purposes, such as sealing of small boxes. The tape can be easily applied with tesa[®] desk dispensers.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	hydrate cellulose	• Total thickness	51 µm
• Type of adhesive	natural & synthetic rubber		

Properties/Performance Values

• Elongation at break	25 %	• Low unwinding force	yes
• Tensile strength	42 N/cm	• Transparency	yes
• Hand tearability	yes		

Adhesion to Values

• Steel	5 N/cm
---------	--------



tesa[®] 4101 PV2

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=04101>