



# tesa<sup>®</sup> Masking Tape Flexible for Curves

## Product Information

BNR 56533, 56534

## Product Description

tesa<sup>®</sup> Masking Tape Curves is a highly flexible masking tape that offers secure masking even on rough surfaces, irregular shapes, curves and sharp edges.

## Product Features

- Enables masking of sharp edges and secure adhesion when stretched
- Super-flexible, even suitable for narrow curves
- Can be used on rough and smooth surfaces
- Residue-free removal for up to 7 days indoors
- Extra-strong adhesion
- Suitable for all paints

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                       |                   |        |
|--------------------|-----------------------|-------------------|--------|
| • Backing          | slightly-creped paper | • Total thickness | 375 µm |
| • Type of adhesive | natural rubber        |                   |        |

## Properties/Performance Values

- |                             |         |                                   |        |
|-----------------------------|---------|-----------------------------------|--------|
| • Tensile strength          | 28 N/cm | • Residue-free removable after... | 7 days |
| • Applicationfield          | Home    |                                   |        |
| • Area of use               | Indoor  | • Reusable                        | no     |
| • Batteries included        | no      | • Spare part service              | no     |
| • Batteries required        | no      | • Tear resistance                 | yes    |
| • Hazard material           | no      | • Tensibility                     | 58 %   |
| • Residue-free removability | yes     | • Writable                        | yes    |



# tesa<sup>®</sup> Masking Tape Flexible for Curves

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>