



Product Information



tesa® 60013 – Self-Adhesive Reinforced Paper Tape

Deskripsi Produk

tesa® 60013 is a high adhesion paper packaging tape featuring a fiberglass reinforced paper backing with a silicone release coating and a solvent-free synthetic rubber adhesive system. tesa® The paper backing for 60013 is reinforced with a fibergalss scrim, making this product the perfect solution for those packaging applications where a secure seal is required. Moreover, tesa®

Sustainable Aspects

- Solvent-free production
- Recycling friendly adhesive does not disturb the paper recycling proces



For more information: https://www.tesa.com/product-sustainability

Product Features

- It provides very strong adhesion and tack on a wide variety of carton qualities and is therefore ideal for the sealing of heavy-weight cartons
- It has excellent adhesion and very agressive tack
- A tamper evidence effect is achieved if this tape is removed from the cardboard

Penerapan

- Suitable for heavy-duty packaging applications (> 25 kg)
- Suitable for packaging applications where a security seal is required (tamper evidence effect)
- High adhesion and very aggresive tack
- High tensile strength
- Suitable for manual and automatic dispensers

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

Type of adhesive

Backing

Paper synthetic rubber Total thickness

210 µm





Product Information

Properti / Nilai Kinerja

•	Elongation at break	6 %
•	Tensile strength	125 N/cm
•	Automatic application	yes
•	Hand tearability	no

Adhesi pada Nilai

Steel 12 N/cm

Additional Information

tesa® 60013 is only available in havana.

,	Low unwinding force	yes
,	Packaging Weight	Up to 25 kg
,	Silent unwinding	yes
,	Solvent free	yes

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit http://l.tesa.com/?ip=60013