

tesa® ACXplus 7043

Product Information



640 µm

640 µm double-sided acrylic core tape

Deskripsi Produk

tesa® ACX^{plus} 704x series is a high-performance acrylic core tape offering two color options to blend in with the bonded substrates. It is a high-performance acrylic core tape for permanent indoor mounting applications.

Product Features

- · Available in gray and white color
- · The color options adapt very well to metal and plastic surfaces to avoid reflections

filled acrylic

Penerapan

Exemplary mounting applications in different industries (e.g. extruder, appliances, interior fit-out, signage) include:

- · Decorative elements
- Touchpanel bonding (e.g. washing machines)

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Ketebalan total

Konstruksi Produk

Penyangga

 Jenis perekat 	pure acrylic		·
Properti / Nilai Kinerja			
 Durasi ketahanan suhu jangka panjang 	110 °C	Durasi ketahanan suhu jangka pendek	200 °C
Adhesion to Values			
Daya rekat ke ABS (awal)	8 N/cm	Daya rekat ke Baja (awal)	17 N/cm
Daya rekat ke ABS (setelah 14 hari)	22 N/cm	 Daya rekat ke Baja (setelah 14 hari) 	29 N/cm
 Daya rekat ke PP (awal) 	1 N/cm	• Daya rekat ke Baja (setelah 3	29 N/cm

Additional Information

hari)

Daya rekat ke PP (setelah 14

The product is recommended for indoor usage. For permanent outdoor applications with load-bearing requirements, our product offer is tesa® ACX^{plus} 707x series. To ensure the highest performance possible, our aim is to fully understand

hari)

1 N/cm



tesa® ACXplus 7043

Product Information

Additional Information

the application (including the substrates involved) to provide the best product recommendation. For more technical data please refer to our technical information sheet on tesa.com/ACX^{plus}.

Liner options:

- PV26: White paper liner unbranded
- PV28: Blue film liner unbranded
- PV48: White film liner branded

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

