



tesa® 51616

Product Information



Pita kain fleece PET tebal untuk peredaman kebisingan tinggi

Deskripsi Produk

tesa® 51616 adalah pita kawat kain fleece PET dengan perekat berbahan dasar karet.

Warna: Hitam

Product Features

- Peredam kebisingan tinggi
- Daya tahan abrasi tinggi
- Dapat disobek dengan tangan

Penerapan

tesa® 51616 dirancang untuk bagian penumpang, yang dapat meredam kebisingan tinggi.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Properti / Nilai Kinerja

- | | | | |
|--|----------------------|--|---------|
| • Perpanjangan saat putus | 50 % | • Ketahanan suhu min. | -40 °C |
| • Kekuatan tarik | 30 N/cm | • Ketahanan terhadap abrasi | Class D |
| • Gaya pelepasan (lebar gulungan < 9 mm) | 12 N/roll (30 m/min) | • Ketahanan terhadap abrasi (mandrel 10 mm, LV312) | Class D |
| • Gaya pelepasan (lebar gulungan > 9 mm) | 12 N/roll (30 m/min) | • Ketahanan terhadap abrasi (mandrel 5 mm, LV312) | Class C |
| • Ketahanan suhu maks. | 105 °C | • Peredaman kebisingan (LV312) | Class D |

Adhesion to Values

- Daya rekat ke Baja 3 N/cm

Additional Information

Lebar standar: 9, 19, 25, 32 mm

Panjang standar: 7,5 m

- Sebagian besar kombinasi lebar dan panjang tersedia

For latest information on this product please visit <http://l.tesa.com/?ip=51616>



tesa® 51616

Product Information

Additional Information

- Dimensi lebih lanjut tersedia berdasarkan permintaan
- Diameter inti standar: 38 mm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=51616>