




tesa® 75815

Product Information



150µm d/s Chemical resistant acrylic foam tape

Deskripsi Produk

tesa® 75815 is a double-sided black tape. It is equipped with a high shock absorbing and chemical resistant adhesive.

Special features:

- Thickness: 150µm
- Excellent chemical resistance
- Very high shock performance
- Good wettability
- High sealing ability with superior waterproof (IPX8)

Penerapan

- Demanding touch panel, lens or screen mounting applications with high requirements for chemical and impact resistance
- Component mounting with high requirements for chemical and impact resistance
- Mounting of 3D or ultra slim bezel designs
- Mounting of waterproof designs

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

• Penyangga	none	• Warna	black
• Jenis perekat	acrylic	• Berat liner	72 g/m ²
• Jenis liner	PET	• Ketebalan liner	50 µm
• Ketebalan total	150 µm	• Warna liner	transparent

Berbagai macam produk

- Ketebalan yang tersedia 50µm, 100µm, 150µm, 200µm

Properti / Nilai Kinerja

- Ageing resistance (UV) very good



tesa[®] 75815

Product Information

Adhesion to Values

- | | | | |
|-------------------------------------|-----------|---------------------------------------|----------|
| • Daya rekat ke PC (awal) | 9.5 N/cm | • Daya rekat ke Baja (awal) | 8.5 N/cm |
| • Daya rekat ke PC (setelah 3 hari) | 16.5 N/cm | • Daya rekat ke Baja (setelah 3 hari) | 9.5 N/cm |

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=75815>