


tesa® 88710

Product Information



250µm Optically Clear Adhesive for Automotive Applications

Deskripsi Produk

887xx Automotive OCA solution provides a wide thickness range together with outstanding ink step coverage feature and reliability performance.

It is a proven solution, well performed at glass/polarizer lamination stack-ups. And it would be suitable for a large and curved display lamination.

Product Features

- PSA type
- High transmission and low haze
- Smooth and easy liner removal
- High bonding strength
- Balanced gap filling and converting performance
- Excellent temperature, humidity and UV resistance

Penerapan

- Automotive Display Lamination
- Curved Glass
- Other optical integration

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

• Penyangga	none	• Ketebalan liner yang mudah dilepas	75 µm
• Jenis perekat	acrylic	• Ketebalan pita	250 µm
• Jenis liner	PET	• Warna liner	transparent
• Warna	transparent	• Warna liner - bagian dalam	transparent
• Ketebalan liner pelepas rapat	100 µm	• Warna liner - bagian luar	transparent

tesa® 88710

Product Information

Properti / Nilai Kinerja

• Ageing resistance (UV)	bagus	• Paku payung	bagus
• Durasi ketahanan suhu jangka panjang	105 °C	• Pelepasan liner - di dalam	tight
• Kabut	0.001 %	• Pelepasan liner - di luar	easy
• Ketahanan terhadap kelembapan	sangat bagus	• Transmittansi (380 - 780 nm) >	99.5 %

Adhesion to Values

• Daya rekat ke Kaca (awal)	10 N/cm
-----------------------------	---------

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=88710>