



tesa® 66514

Product Information



Optical Clear Display Protection Film

Deskripsi Produk

tesa® 66514 is a single coated adhesive tape used for the protection of high gloss LCD display hard lenses of electronic and communication devices during assembly, inspection, storage and transport.

The tape consists of a PET backing coated with an acrylic adhesive. It is equipped with a transparent 50µm PET release liner providing easy peel-off.

Product Features

- High transparency providing excellent visibility of final display.
- Secure protection of display surfaces.
- Easy peel-off release liner with good die-cut abilities.
- Suitable to various smooth surfaces like Glass, ABS or PC.
- Easy to remove even after long cycle applications.
- 300h weathering resistance according ISO 4892-2.

Penerapan

Protection of high gloss LCD display hard lenses of electronic and communication devices during assembly, inspection, storage and transport.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

• Penyangga	PET film	• Warna	transparent
• Jenis perekat	acrylic	• Ketebalan liner	50 µm
• Jenis liner	PET	• Warna liner	transparent
• Ketebalan total	40 µm		

Adhesion to Values

• Daya rekat ke ABS (awal)	0.1 N/cm	• Daya rekat ke PC (awal)	0.1 N/cm
• Daya rekat ke ABS (setelah 14 hari)	0.1 N/cm	• Daya rekat ke PC (setelah 14 hari)	0.1 N/cm
• Daya rekat ke Kaca (awal)	0.1 N/cm	• Daya rekat ke Baja (awal)	0.1 N/cm
• Daya rekat ke Kaca (setelah 14 hari)	0.1 N/cm	• Daya rekat ke Baja (setelah 14 hari)	0.1 N/cm



tesa® 66514

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=66514>