




tesa® 60371

Product Information



30µm double sided black electrically conductive non-woven tape

Deskripsi Produk

tesa® 60371 is a black double sided electrically conductive self adhesive tape. It consists of an electrically conductive non-woven backing and an electrically conductive acrylic adhesive.

Black color

Product Features

- Enhanced electrical conductivity in XYZ-direction
- Highly reliable and stable conductivity even after damp heat conditions* Good bonding strength
- Great conformability and adjustment to uneven surfaces
- Excellent grounding performance at small bonding area

Penerapan

- EMC applications
- Main board, FPC grounding
- Antenna grounding
- Electrostatic discharge applications

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

- | | | | |
|-------------------|----------------------|-------------------|-------------|
| • Penyangga | conductive non-woven | • Warna | black |
| • Jenis perekat | conductive acrylic | • Ketebalan liner | 50 µm |
| • Jenis liner | PET | • Warna liner | transparent |
| • Ketebalan total | 30 µm | | |

Properti / Nilai Kinerja

- | | | | |
|---------------------------------------|------------------------|--|-----------|
| • Durasi ketahanan suhu jangka pendek | 200 °C | • Ketahanan terhadap geser statis pada suhu 40 # | very good |
| • Ketahanan kontak arah-z (awal) | 0.01 Ohm / square inch | • Pelepasan liner | easy |
| • Ketahanan permukaan arah x-y | 0.1 mOhm | | |



tesa[®] 60371

Product Information

Adhesion to Values

- Daya rekat ke Baja (setelah 14 hari) 5.1 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60371>