

tesa® 52995

Product Information



Top-coated Permanent Surface Protection Film

Deskripsi Produk

tesa® 52995 is a single sided transparent protection film with a clear high gloss top coated aliphatic polyurethan backing, a permanent acrylic adhesive and a polyester liner.

Product Features

- Highly transparent product design
- Resistant and durable against mechanical and environmental forces
- Additional topcoat provides outstanding gloss and enhances its exterior durability
- long-term UV resistance and self-healing properties without turning yellow over the vehicle's lifetime
- Good conformability makes it ideal for curves and complex surface geometries
- Dimension stability and die-cuttablity
- Compatible with several paint and clearcoat systems

Penerapan

tesa® 52995 is applied to permanently protect sensitive surfaces against strong mechanical forces in interior and exterior applications. It is specially designed for permanent paint protection against stone chipping, abrasion, scratches and corrosion in automotive applications e.g.

- wheel arches
- door edges
- side skirts
- door sill trims
- trunk edges
- front and rear bumpers
- VIN labels
- ...

Due to its good conformability, it can be applied to even and slightly curved surfaces.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

• Penyangga	PU film	• Ketebalan total	280 µm
• Jenis perekat	acrylic	• Warna	transparent
• Jenis liner	PET	• Warna liner	translucent

tesa® 52995

Product Information

Berbagai macam produk

- | | | | |
|---------------------------|-------------|------------------------|--------------|
| • Ketebalan yang tersedia | 280, 330 µm | • Format yang tersedia | 50m x 1245mm |
|---------------------------|-------------|------------------------|--------------|

Properti / Nilai Kinerja

- | | | | |
|------------------------------|-----------|----------------------------------|-----------|
| • Kekuatan tarik | 50 N/cm | • Ketahanan suhu (30 menit) | 90 °C |
| • Cocok untuk pemotongan die | yes | • Ketahanan terhadap abrasi | yes |
| • Hasil akhir permukaan doff | no | • Ketahanan terhadap bahan kimia | very good |
| • Kesesuaian | very good | • Ketahanan terhadap gores | very good |
| • Ketahanan suhu | yes | • Permukaan akhir mengkilap | yes |

Kondisi penyimpanan

Kondisi penyimpanan

If stored under proper conditions, product retains its performance and properties for 12 months from date of delivery.

Additional Information

Customized shapes and sizes as die cut solutions are available as tesa® 54995.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=52995PV0>