


tesa® 60412

Product Information



Recycled PET Packaging Tape

Deskripsi Produk

tesa® 60412 is a general-purpose packaging tape based on a 70% Post-Consumer Recycled (PCR) PET backing and a water-based acrylic adhesive system. tesa® 60412 has a strong and abrasion resistant backing with excellent bearing and wear properties. It features a very consistent, pressure sensitive acrylic adhesive, making this product the perfect solution for light- and medium-weight packaging application (max. 30 kg). The material combination guarantees a low noise unwind and an excellent printability with all types of ink systems.

tesa® 60412 not only provides an outstanding performance, but it is also an advanced alternative contributing to sustainability:

- The backing material is made of post-consumer recycled PET (70% recycled content).
- This product can be disposed together with the box into the blue bin without endangering the cardboard recycling process (certified according to INGEDE method 12).
- The production process of this product is solvent-free

tesa® 60412 grants a very good performance on recycled cardboards.

Berkelanjutan Aspek



Untuk informasi lebih lanjut: <https://www.tesa.com/product-sustainability>

Penerapan

- Sealing of cardboxes
- Suitable for light- and medium-weight packaging applications (max. 30 kg)
- Excellent adhesion in recycled cardboards
- Suitable for manual and automatic dispensers
- Brand showcase and advertising purposes

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

• Penyangga	PET	• Jenis perekat	water-based acrylic
• Berbasis Bio (konten karbon-bio)	90 %	• Ketebalan total	56 µm

tesa® 60412

Product Information

Berbagai macam produk

- Warna yang tersedia transparent, white, brown

Properti / Nilai Kinerja

- | | | | |
|----------------------------------|-------------|-----------------------------------|--------------------|
| • Perpanjangan saat putus | 130 % | • Informasi Transportasi | Temperature 0-70°C |
| • Kekuatan tarik | 60 N/cm | • Kemampuan disobek dengan tangan | low |
| • Aplikasi otomatis | no | • Ketahanan terhadap kelembapan | yes |
| • Berat Kemasan | Up to 30 kg | • Melepas tanpa suara | yes |
| • Cocok untuk pembekuan mendalam | yes | | |

Adhesion to Values

- Daya rekat ke Baja 3 N/cm

Sertifikat

Sertifikat Berkelanjutan

- Tested according to INGEDE method 12. Test report available

Additional Information

Available in transparent. Chamois and white are available upon request.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60412>