

tesa® 61346

Product Information



Pita perekat penutup dua sisi berbasis kertas

Deskripsi Produk

tesa® 61346 adalah pita perekat dua sisi berwarna putih, yang terdiri atas kertas penyangga dan perekat karet sintetis yang seimbang.

Berkelanjutan Aspek



Untuk informasi lebih lanjut: <https://www.tesa.com/product-sustainability>

Product Features

- Pita perekat penutup dua sisi berbasis kertas
- Perekat yang seimbang menawarkan daya rekat yang tinggi pada bahan karton yang umum digunakan dan kekuatan geser yang sangat baik
- Bagian belakang kertas yang kuat untuk kinerja penutupan kotak yang andal
- Pelapis kertas untuk menahan pelepasan liner yang cepat tanpa sobek
- Pelepasan yang mulus dan kemampuan proses yang telah terbukti pada aplikator pita perekat standar pasar
- Dibuat dengan kertas dari hutan bersertifikat yang dikelola dengan baik dan sumber terkontrol lainnya

Penerapan

- Untuk aplikasi penutupan bahan kertas, karton, atau kardus bergelombang
- Tujuan umum pita perekat pemasangan
- Cocok untuk aplikasi otomatis

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

- | | | | |
|-------------------|------------------|-------------------|----------------------|
| • Penyangga | Paper | • Warna | white |
| • Jenis perekat | synthetic rubber | • Berat liner | 102 g/m ² |
| • Jenis liner | glassine | • Ketebalan liner | 84 µm |
| • Ketebalan total | 185 µm | • Warna liner | white |

tesa® 61346

Product Information

Properti / Nilai Kinerja

- | | | | |
|---------------------------|---------|-----------------------------------|--------------|
| • Perpanjangan saat putus | 1.7 % | • Ketahanan terhadap geser statis | sangat bagus |
| • Kekuatan tarik | 40 N/cm | • Ketahanan terhadap geser statis | rendah |
| • Ageing resistance (UV) | rendah | pada suhu 40 # | |
| • Bebas pelarut | yes | • Ketahanan terhadap | sedang |
| | | kelembapan | |
| | | • Paku payung | bagus |

Adhesion to Values

- | | | | |
|----------------------|---------|-----------------------------|---------|
| • Daya rekat ke Baja | 10 N/cm | • Daya rekat ke Baja (awal) | 10 N/cm |
|----------------------|---------|-----------------------------|---------|

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=61346>