

tesa® 60408

Bio-based paper packaging tape

Product Information



Deskripsi Produk

tesa® 60408 is a paper-based packaging tape featuring a premium paper backing and a well-performing waterborne natural rubber adhesive. The paper backing of tesa® 60408 is made with paper from well-managed forests and other controlled sources. This premium paper backing is tear-resistant with a high tensile strength. Thanks to the silicone-free release coat, a very good printability with all types of ink systems is secured (externally tested). The well-performing natural rubber adhesive system provides strong adhesion and a good initial tack on a wide variety of carton qualities. tesa® 60408 is the perfect solution for light- and medium-weight packaging applications (max. 20 kg) where a premium performance is required.

Berkelanjutan Aspek

- The paper backing is made with paper from well-managed forests and other controlled sources
- 92% bio-based carbon content in total product (certified by DIN CERTCO)
- Highest bio-based carbon content rating from DIN CERTCO
- Recycling-friendly according to INGEDE method 12 (78/100)
- Solvent-free production process



Untuk informasi lebih lanjut: <https://www.tesa.com/product-sustainability>

Penerapan

- Ideal for the sealing of cardboard boxes up to 20 kg
- Suitable for manual and automatic applications
- Printable with all types of ink systems

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

- | | | | |
|-----------------|----------------|---|--------|
| • Penyangga | Paper | • Persentase total kandungan karbon dari bahan hayati (tidak termasuk liner, sesuai ASTM D6866) | 89 % |
| • Jenis perekat | natural rubber | • Ketebalan total | 125 µm |

Berbagai macam produk

- Warna yang tersedia
- brown

tesa® 60408

Bio-based paper packaging tape

Product Information

Properti / Nilai Kinerja

- | | | | |
|---------------------------|-------------|--------------------------------------|-----------|
| • Perpanjangan saat putus | 8 % | • Kemampuan disobek dengan tangan | dan |
| • Kekuatan tarik | 60 N/cm | • Kemampuan untuk dicetak | very good |
| • Aplikasi otomatis | yes | • Ketahanan terhadap kelembapan | sedang |
| • Bebas pelarut | yes | • Pembukaan dengan kebisingan rendah | yes |
| • Berat Kemasan | Up to 20 kg | | |

Adhesion to Values

- Daya rekat ke Baja 2.8 N/cm

Sertifikat

Sertifikat Berkelanjutan

- Total bio-based content >85% certified by DIN Certco

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60408>