

tesa® Professional 4334

Product Information

High grade paint tape for precise and flat paint edges

Deskripsi Produk

The tesa® 4334 Precision Mask® tape works right along the line, and provides the best basis for professional painting work both indoors and outdoors. The extremely thin paper backing, coated with a special acrylic adhesive, ensures razor-sharp paint edges and protects the base surface from paint spatters. The masking tape is also suitable for masking surfaces during spray painting and subsequent drying at up to 120°C. Thanks to the tape's high quality, there'll be no costly, time-consuming retouching to do.

Product Features

- Indoor masking (up to 6 months)
- Outdoor masking (up to 8 weeks)
- For smooth and slightly textured surfaces
- For high-quality painting and lacquering work
- For spray painting with afterwards oven drying up to 120°C/30 min
- Made with paper sourced from responsibly managed forests and other controlled sources

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

- | | | | |
|-----------------|-------------|-------------------|-------|
| • Penyangga | Washi paper | • Ketebalan total | 90 µm |
| • Jenis perekat | acrylic | | |

Properti / Nilai Kinerja

- | | | | |
|---------------------------|---------|-----------------------------------|--------------|
| • Perpanjangan saat putus | 4 % | • Kemampuan disobek dengan tangan | sangat bagus |
| • Kekuatan tarik | 30 N/cm | • Ketahanan suhu (30 menit) | 150 °C |

Adhesion to Values

- | | |
|----------------------|----------|
| • Daya rekat ke Baja | 1.8 N/cm |
|----------------------|----------|

tesa® Professional 4334

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4334>