

tesa® 4661

Product Information



Berkelanjutan Aspek

- 64% bio-based carbon content (DIN EN 16640)



Untuk informasi lebih lanjut: <https://www.tesa.com/product-sustainability>

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

- | | | | |
|-----------------|----------------------|---|--------|
| • Penyangga | Acrylic-coated cloth | • Persentase total kandungan karbon dari bahan hayati (tidak termasuk liner, sesuai DIN EN 16640) | 64 % |
| • Jenis perekat | natural rubber | • Ketebalan total | 300 µm |

Properti / Nilai Kinerja

- | | | | |
|---|---------------------------|-----------------------------|--------------|
| • Perpanjangan saat putus | 12 % | • Ketahanan terhadap abrasi | sangat bagus |
| • Kekuatan tarik | 100 N/cm | • Ketahanan terhadap air | bagus |
| • Jaring | 145 count per square inch | • Mudah ditulis | yes |
| • Kemampuan disobek dengan tangan | sangat bagus | • Tepi sobekan lurus | sangat bagus |
| • Ketahanan suhu (kemampuan perpindahan dari aluminium setelah terpapar 30 menit) | 140 °C | | |

Adhesion to Values

- | | |
|----------------------|----------|
| • Daya rekat ke Baja | 5.8 N/cm |
|----------------------|----------|

tesa® 4661

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4661>