

tesa® 4150 Masking tape

tesa® 4150 is a masking tape with a PVC-backing and age-resistant acrylic adhesive.

Main Application

Masking tape for wide range of masking requirements

Technical Data

| | | | |
|--------------------|----------|-----------------------|---------|
| ▪ Backing material | PVC film | ▪ Adhesion to steel | 4 N/cm |
| ▪ Total thickness | 70 µm | ▪ Elongation at break | 70 % |
| ▪ Type of adhesive | acrylic | ▪ Tensile strength | 53 N/cm |

Properties

| | | | |
|------------------|-----|-----------------------|-----|
| ▪ Easy to remove | yes | ▪ Conformability | ●●● |
| ▪ Printability | ●●● | ▪ Low unwinding force | ●●● |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04150>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.