

tesaflex® 4163 Multipurpose Soft PVC Premium

tesaflex® 4163 permits is a special formulated Soft PVC tape with a good film flexibility. Due to the UV stable acrylic adhesive it is perfect suitable for permanent applications.

Main Application

tesaflex® 4163 is universal useable and exceptionally qualified for general jobs like:

- Installation
- Repairing
- Marking
- Splicing
- Bundling

Technical Data

▪ Backing material	soft PVC	▪ Tensile strength	30 N/cm
▪ Total thickness	130 µm	▪ Type of liner	re pulpable siliconised paper
▪ Type of adhesive	acrylic	▪ Temperature resistance	105 °C
▪ Adhesion to steel	1.8 N/cm	▪ UV-resistance	104 weeks
▪ Elongation at break	250 %	▪ Dielectric breakdown voltage	7000 volt

Properties

- Certified according to US 302

Additional Information

It conforms to US safety standard 302. The isogenogrey colour is perfect suitable for instalation of water pipes.

For latest information on this product please visit <http://l.tesa.com/?ip=04163>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.