

## tesa® 4182 PV2

### Soft PVC film tape for standard wrapping

tesa® 4182 PV2 is a PVC film wire harness tape with an acrylic adhesive.

#### Major Features:

- Temperature resistance 105°C/3000h
- Flexible
- Handtearable

Color: Black

### Main Application

tesa® 4182 PV2 is designed for the passenger compartment for standard wrapping up to a temperature class of 105°C.

### Technical Data

▪ Backing material	PVC film	▪ Temperature resistance (3000h)	105 °C
▪ Total thickness	104 µm	▪ Abrasion resistance (10mm mandrel)	Class A (acc. to LV312)
▪ Type of adhesive	acrylic	▪ Abrasion resistance (5mm mandrel)	Class A (acc. to LV312)
▪ Adhesion to steel	1.8 N/cm	▪ Flame resistance as composite	Class B (acc. to LV312)
▪ Elongation at break	250 %	▪ Unwind force (roll width > 9mm)	7.5 N/roll (30 m/min)
▪ Tensile strength	25 N/cm	▪ Noise damping (decibel)	Class A (acc. to LV312)
▪ Temperature resistance min.	-25 °C		

### Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 33 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 38 mm

For latest information on this product please visit <http://l.tesa.com/?ip=04182>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.