

tesa® 4302

High performance paper masking tape up to 160 °C

tesa® 4302 is a finely crêped and good conformable paper masking tape, especially suitable for the highest requirements of automotive paintworks (water- or solvent based paints) followed by oven-drying.

Paints and even critical filler systems adhere excellent to the backing avoiding any kind of flaking.

tesa® 4302 can be removed from rubber, glass and paint without tearing or leaving adhesive residues. This is specially remarkable even for cold removal after high heat cycles.

Due to its finely crêped structure, this tape guarantees sharp edged finishing.

Technical Data

▪ Backing material	slightly-creped paper	▪ Elongation at break	10 %
▪ Total thickness	170 µm	▪ Tensile strength	46 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance	160 °C
▪ Adhesion to steel	4 N/cm		

Properties

▪ Hand tearability	●●●●	▪ Sharp colour edge	●●●
▪ Easy to remove	yes	▪ Conformability	●●●
▪ Paint anchorage	●●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04302>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.