

## tesa® 4423

### Paper Stencil Material for Short Term Sandblasting Applications

This tape is suited for almost all paint applications during construction or renovating ships and boats. It is suitable for a variety of common surfaces such as glass, aluminium, wood and especially hard-PVC.

### Main Application

Closing and reinforcing of shipping cartons

### Technical Data

▪ Backing material	flat paper	▪ Elongation at break	5 %
▪ Total thickness	145 µm	▪ Tensile strength	57 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance	60 °C
▪ Adhesion to steel	4.5 N/cm		

### Properties

▪ Hand tearability	●●●●	▪ Paint anchorage	●●●●
▪ Plottability	●●●	▪ Sharp colour edge	●●●●
▪ Suitable for sandblasting	●●	▪ Conformability	●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

### Additional Information

The unique features of tesa® 4423 offer further benefits: \*Can be peeled off easily \*Pliable and easy to cut by hand \*Will not distort when used for long straight lines (e.g. for masking of water lines in boat building or multi-colour painting of narrow stripes)

For latest information on this product please visit <http://l.tesa.com/?ip=04423>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.