

tesa® 4660

Printable acrylic coated cloth tape

tesa® 4660 is a special acrylic coated cloth tape with a printable surface. It is based on a 145 mesh woven cotton fabric backing and a thermosetting natural rubber adhesive.

tesa® 4660 is a flexible but also strong tape.

Features:

- high adhesion on almost every surface
- removable without residues
- excellent flexo printable surface
- high temperature resistance
- very high tensile strength
- excellent tape for die-cuts, available with liner as tesa® 4660 PV9
- available in 2 colours: white and yellow

Main Application

tesa® 4660 is mostly used for wire marking and other elements identification of electric devices.

- Bundling and marking of cable harnesses for electrical equipment and insulation
- Marking in switch boxes
- Marking in electrical components
- Closing of tins and tubes
- Labelling with printed die-cuts
- Window flange

Technical Data

▪ Backing material	acrylic-coated cloth	▪ Elongation at break	7.5 %
▪ Total thickness	262 µm	▪ Tensile strength	100 N/cm
▪ Type of adhesive	thermosetting natural rubber	▪ Temperature resistance (30 min)	180 °C
▪ Adhesion to steel	4 N/cm	▪ Mesh	145 count per square inch

Properties

▪ Hand tearability	●●●●	▪ Easy to write on	yes
▪ Straight tear edges	●●●●	▪ Suitable for die cutting	yes
▪ Easy to remove	yes	▪ Abrasion resistance	●●●●
▪ Printability	●●●●	▪ Water resistance	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04660>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.