productinformation

tesa® 4661

Standard acrylic coated cloth tape

tesa® 4661 is a strong acrylic coated cloth tape. It is based on a 148 mesh woven rayon fabric backing and a natural rubber adhesive.

tesa® 4661 is an all-round cloth tape for a wide range of applications, often used for belting of components.

Features:

- high adhesion, even on rough surfaces
- very high tensile strength
- abrasion-resistant
- available in 7 colors: black, white, grey, yellow, blue, red, green

Main Application

- Marking of wires and cables
- Bundling of pipes, profiles etc.
- Noise and scrub protection
- Harnessing
- Colour coding
- Securing of sharp edges
- Sealing of cartons, tins and tubes
- Belting of components, nails, screws, bicylce rims etc.
- Floor marking
- Sandblasting
- Floor coating

Technical Data

	Backing	material
--	---------	----------

Total thickness

Type of adhesive

Adhesion to steel

acrylic-coated cloth

300 um

natural rubber

5.8 N/cm

Elongation at break

Tensile strength Temperature resistance (30 min)

Mesh

12 %

100 N/cm

140 °C

145 count per square

inch

Properties

- Hand tearability
- Straight tear edges
- Easy to remove
- Easy to write on

- Available as Spools
- Abrasion resistance
- Water resistance

Evaluation across relevant tesa® assortment: • • • • very good

For latest information on this product please visit http://l.tesa.com/?ip=04661

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

