

## tesa® 51007

### PET cloth tape for abrasion protection

tesa® 51007 is a PET cloth wire harness tape with a rubber based adhesive.

#### Major Features:

- High temperature resistance 150°C/3000h
- Abrasion resistant
- Strong adhesion

Color: Black

### Main Application

tesa® 51007 is designed for the engine compartment, providing abrasion protection. Specifically made for automatic bundling

### Technical Data

▪ Backing material	PET cloth	▪ Temperature resistance (3000h)	150 °C
▪ Total thickness	320 µm	▪ Abrasion resistance (10mm mandrel)	Class C (acc. to LV312)
▪ Type of adhesive	rubber based	▪ Abrasion resistance (5mm mandrel)	Class B (acc. to LV312)
▪ Adhesion to steel	4.5 N/cm	▪ Flame resistance as composite	Class B (acc. to LV312)
▪ Elongation at break	22 %	▪ Unwind force (roll width ≤ 9mm)	6 N/roll (30 m/min)
▪ Tensile strength	175 N/cm	▪ Unwind force (roll width > 9mm)	6 N/roll (30 m/min)
▪ Temperature resistance min.	-40 °C	▪ Noise damping (decibel)	Class A (acc. to LV312)

### Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 50 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 76 mm
- Applicable for red ring assembly aid

For latest information on this product please visit <http://l.tesa.com/?ip=51007>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.