

tesa Sleeve® 51026 PV5

PET cloth Sleeve for abrasion protection and enhanced flexibility

tesa Sleeve® 51026 PV5 is a PET cloth Sleeve coated at the edges with an acrylic adhesive for spiral application.

Major Features:

- High temperature resistance 150°C/3000h
- High flexibility
- Exceptionally high abrasion resistance

Color: Black

Main Application

tesa Sleeve® 51026 PV5 is designed for the engine compartment, providing superior abrasion protection and flexibility. It combines the well known spiral application of a tape with the flexibility of a sleeve

Technical Data

▪ Backing material	PET cloth	▪ Temperature resistance (3000h)	150 °C
▪ Total thickness	530 µm	▪ Abrasion resistance (10mm mandrel)	Class E (acc. to LV312)
▪ Type of adhesive	acrylic	▪ Abrasion resistance (5mm mandrel)	Class D (acc. to LV312)
▪ Adhesion to steel	5.5 N/cm	▪ Flame resistance as composite	Class B (acc. to LV312)
▪ Temperature resistance min.	-40 °C	▪ Noise damping (decibel)	Class B (acc. to LV312)

Additional Information

Standard widths: 45, 59 mm

Standard lengths: 10, 15 m

- Most combinations of width and length are possible
- Standard core diameter: 38 mm

For latest information on this product please visit <http://l.tesa.com/?ip=51026>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.