

tesa Sleeve® 51036 PV9

PET cloth Sleeve for enhanced flexibility

tesa Sleeve® 51036 PV9 is a PET cloth coated at the edges with an advanced acrylic adhesive (Triple A®) for lengthwise application.

Major Features:

- High temperature resistance 150°C/3000h
- High flexibility
- Abrasion resistant
- Easy and efficient lengthwise application

Color: Black

Main Application

tesa Sleeve® 51036 PV9 is designed for the engine compartment, providing high flexibility.
For lengthwise application

Technical Data

▪ Backing material	PET cloth	▪ Temperature resistance (3000h)	150 °C
▪ Total thickness	220 µm	▪ Abrasion resistance (10mm mandrel)	Class C (acc. to LV312)
▪ Type of adhesive	acrylic	▪ Abrasion resistance (5mm mandrel)	Class B (acc. to LV312)
▪ Adhesion to steel	5 N/cm	▪ Flame resistance as composite	Class B (acc. to LV312)
▪ Temperature resistance min.	-40 °C	▪ Noise damping (decibel)	Class A (acc. to LV312)

Additional Information

Standard widths: 68, 78, 100, 130, 155, 195 mm

Standard lengths: 50 m

- Most combinations of width and length are possible
- Also available with customized perforation

Harness diameter / tesa Sleeve® width recommendation

< Ø 13 mm / 68 mm
Ø 13 mm – 16 mm / 78 mm
Ø 16 mm – 23 mm / 100 mm
Ø 23 mm – 33 mm / 130 mm
Ø 33 mm – 41 mm / 155 mm
Ø 41 mm – 54 mm / 195 mm

- Standard core diameter: 76 mm

For latest information on this product please visit <http://l.tesa.com/?ip=51036>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.