

## tesa EasySplice® 51150 FastLine Repulpable, double-sided splicing tape

tesa® 51150 EasySplice® FastLine is a repulpable double-sided integrated flying splice tape consisting of a flat-back paper and a modified water soluble acrylic adhesive

tesa® 51150 EasySplice® FastLine features especially:

- Highest tack properties
- Very good adhesion values on coated and uncoated paper
- Low splice thickness
- Printable and coatable backing
- Good repulpability over full pH-range (pH3 – pH9)

Following functions are provided:

- Slit liner for the secure fixation of the top sheet
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- Two splitting strips with paper backing for a smooth opening of the new paper reel without jeopardizing the coating process

Colour: Blue

## Main Application

tesa® 51150 EasySplice® FastLine is particularly suitable for:

- Flying splices at fast running off-line coaters

## Technical Data

▪ Backing material	flat paper	▪ Tensile strength	30 N/cm
▪ Total thickness	100 µm	▪ Type of liner	repulpable siliconised paper
▪ Type of adhesive	repulpable tackified acrylic	▪ Shelf life time (packed) < 25°C	12 months
▪ Elongation at break	6 %		

## Properties

- |        |     |                           |    |
|--------|-----|---------------------------|----|
| ▪ Tack | ●●● | ▪ Static shear resistance | ●● |
|--------|-----|---------------------------|----|

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=51150>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.