

## tesa® 51207

### Special sliding PE-UHMW tape for anti-squeak prevention and abrasion protection

tesa® 51207 is a thin UV and abrasion resistant high density PE tape with excellent adhesive power. The product is optimized for the automotive industry to protect components, trim parts and harnesses against mechanical damage in combination with noise prevention.

#### Features:

- Transparency and UV resistance assist the application in the visible area
- Self-lubricating tape with very good sliding properties reduces wear and friction and prevents noise
- High energy absorption capacity even at high stress levels

## Main Application

tesa® 51207 is especially designed for interior and exterior anti-squeak and abrasion protection at the assembly line to ensure a reliable:

- Masking of sharp-edged sheet-metal components
- Sliding of car roofs, slide doors, delicate components
- Prevention of noise and wear, e.g. from trim parts
- Protection of harnesses in high friction areas
- Application in visible areas e.g. bumper, B-pillar, wheel house

## Technical Data

▪ Backing material	PE	▪ Adhesion to steel	4.3 N/cm
▪ Color	transparent	▪ Elongation at break	340 %
▪ Total thickness	114 µm	▪ Tensile strength	53 N/cm
▪ Type of adhesive	pure acrylic	▪ Type of liner	glassine

## Properties

▪ Abrasion resistance	●●●●	▪ Noise reducing	●●●
▪ Conformability	●●●●	▪ Self-lubricating properties	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

## Additional Information

Very good UV resistance: > 1000h WOM Florida test

1000h WOM Florida test

The material can be supplied as die cuts in roll or sheets individually to customer specific dimensions under tesa® 54207 tesa's automation and application solution department provides customized equipment and self-designed application tools to enhance productivity.

For latest information on this product please visit <http://l.tesa.com/?ip=51207>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.