

## tesa® 51324 tesa® 4324 as SAF

tesa® 51324 is a finely crêped and wet resistant paper masking tape with a good flexibility and a high tensile strength.

### Main Application

tesa® 4324 is suitable for masking during paint spraying with oven drying (up to 80 °C).

Further applications are e.g.:

- bandoliering of yarn beams
- splicing of photo papers and veneers
- coil bandages

### Technical Data

▪ Backing material	slightly-creped paper	▪ Elongation at break	17 %
▪ Total thickness	280 µm	▪ Tensile strength	47 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance	80 °C
▪ Adhesion to steel	4 N/cm		

### Additional Information

The flexibility and the soft adhesive allow good adhesion to rough surfaces or complicated shapes and contours.

For latest information on this product please visit <http://l.tesa.com/?ip=51324>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.