productinformation

tesa® 51432

Extra strong bandoliering tape for heavy components

For storage- and sequenzer-bandoliering in combination with crêped bandoliering tape.

Main Application

The dimensionally stable smooth paper backing makes the product particularly suitable for bandoliering of heavy components.

Especially for sequenzer bandoliering, where more rigid belts are needed.

Technical Data

▪ Backing material	flat paper	▪ Elongation at break	6 %
▪ Total thickness	330 µm	▪ Tensile strength	93 N/cm
▪ Type of adhesive	natural rubber	▪ Temperature resistance	100 °C
▪ Adhesion to steel	8 N/cm		

Additional Information

tesa® 51432 may be combined with tesa® 51300 or 51316.

For latest information on this product please visit http://l.tesa.com/?ip=51432

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

tesa® great to work with