

## tesa® 51570

### Double-sided non-woven tape

tesa® 51570 is a double-sided tape with a non-woven backing. It is used for permanent mounting of metal and plastic materials, e.g. aluminum, polystyrene, polypropylene, ABS. The thick layer of adhesive bonds well on uneven surfaces and has a very high initial bond.

## Main Application

General purpose mounting

## Technical Data

▪ Backing material	non-woven	▪ Type of adhesive	synthetic rubber
▪ Total thickness	110 µm		

## Adhesion to

▪ Steel (initial)	12.0 N/cm	▪ Steel (after 14 days)	13.0 N/cm
▪ PE (initial)	5.5 N/cm	▪ PE (after 14 days)	7.0 N/cm
▪ PP (initial)	7.0 N/cm	▪ PP (after 14 days)	12.0 N/cm
▪ PS (initial)	8.0 N/cm	▪ PVC (after 14 days)	12.5 N/cm
▪ PVC (initial)	9.0 N/cm		

## Properties

▪ Temperature resistance short term	80 °C	▪ Resistance to chemicals	●
▪ Temperature resistance long term	40 °C	▪ Softener resistance	●
▪ Tack	●●●●	▪ Static shear resistance at 23°C	●●●
▪ Ageing resistance (UV)	●●	▪ Static shear resistance at 40°C	●
▪ Humidity resistance	●●●	▪ Fogging	●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

## Additional Information

It is not recommended to apply tesa® 51570 where a temperature load of over 60° C prevails for a longer period.

For latest information on this product please visit <http://l.tesa.com/?ip=51570>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.