

tesa® 51916

Repulable, Transfer Splicing Tape

tesa® 51916 is a very thin double-sided repulable transfer tape consisting of a modified water soluble acrylic adhesive.

tesa® 51916 features especially

- Very high shear strength
- Very good adhesion values on coated and uncoated paper
- Very low splice thickness
- Very high heat resistance
- Good repulpability over full pH-range (pH3 –pH9)

Colour: Blue, Colourless

Main Application

tesa® 51916 is particularly suitable for

- Permanent overlapped splices
- The use in hand dispensers or automatic applying processes
- Splicing of carbonless paper

Technical Data

▪ Backing material	none	▪ Type of liner	repulable
▪ Total thickness	50 µm	▪ Shelf life time (packed) < 25°C	siliconised paper
▪ Type of adhesive	repulable tackified acrylic		12 months

Properties

- | | | | |
|--------|-------|---------------------------|---------|
| ▪ Tack | ● ● ● | ▪ Static shear resistance | ● ● ● ● |
|--------|-------|---------------------------|---------|

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=51916>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.