

tesa® 53000 PV1

High strength tape for low energy surfaces

tesa® 53000PV1 combines a revolutionary new backing, with a high-performance synthetic rubber adhesive system, specially designed for low energy surfaces.

The heavy duty TPP (tensilized polypropylene) backing is specially oriented to provide high tensile strength in a thinner backing than traditional TPP tapes. In addition, the orientation is such that the elongation is dramatically reduced, up to half of that of traditional TPP tapes.

The synthetic rubber adhesive system provides a secure bond to difficult surfaces, yet removes clean off the surface, without adhesive residue, and filament delamination -a common problem of filament tapes.

Main Application

- Temporary holding of appliance parts
- Temporary holding on powder coated surfaces

Technical Data

▪ Backing material	MOPP	▪ Adhesion to steel	7 N/cm
▪ Total thickness	127 µm	▪ Elongation at break	18 %
▪ Type of adhesive	synthetic rubber	▪ Tensile strength	300 N/cm

Properties

▪ Residue free removal	yes	▪ No discolouration	yes
------------------------	-----	---------------------	-----

For latest information on this product please visit <http://l.tesa.com/?ip=53000>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.