

## tesa® 60058 Spacer Tape

7900µm double sided high density PU foam tape

tesa® 60058 is a double sided open cell PU foam tape. The tape is equipped with an acrylic adhesive. The open cell PU foam allows an air and moisture transport through the tape, permitting an optimum silicone curing.

### Main Application

tesa® 60058 was designed as a spacer element for two- and four- sided structural glazing systems. The tape creates a gap of the correct dimensions for the silicone adhesive.

### Technical Data

▪ Backing material	PU foam	▪ Type of liner	PE
▪ Color	black	▪ Colour of liner	blue
▪ Total thickness	7900 µm	▪ Thickness of liner	100 µm
▪ Type of adhesive	acrylic		

### Adhesion to

- Steel (after 14 days) 2.3 N/cm

### Additional Information

- Density (ASTM D3574): 248 kg/m<sup>3</sup>
- Shore A Hardness (ASTM D2240): 31
- Compression Deflection @10%: 99 kPa
- Tensile Strength (ASTM D3574): 1103 kPa
- Elongation (ASTM D3574): 105%
- Thermal Conductivity (ASTM): 0.39 (BTU·in/h·ft<sup>2</sup>·°F)
- Available Widths: 6mm - 1372mm

For latest information on this product please visit <http://l.tesa.com/?ip=60058>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.