

tesa® 60233

60µm single sided matte black electrically conductive tape xy-axis

tesa® 60233 is a matte black single sided electrically conductive self adhesive tape. It consists of a matte black PET backing which is laminated with an Aluminium foil and a conductive non-woven. The backing is coated on the non-woven side with an electrically conductive adhesive.

tesa® 60233 features especially:

- Thickness: 60µm
- Excellent electrical conductivity in XY-direction for very good grounding performance
- PET film on the surface provides insulation function
- High adhesion level even at harsh environmental conditions avoids edge lifting
- Minimized curling for easy processing and lamination
- Matte black surface (low gloss) with anti-finger print and solvent resistant characteristic

Main Application

- Grounding of LCD to metal BLU chassis

Technical Data

▪ Backing material	Black PET / alu foil / conductive non-woven	▪ Colour of liner	white/blue logo
▪ Color	matte black	▪ Thickness of liner	50 µm
▪ Type of adhesive	conductive acrylic	▪ Release of liner	easy
▪ Adhesion to Steel (initial)	4.4 N/cm	▪ Temperature resistance short term	200 °C
▪ Adhesion to Steel (after 14 days)	5 N/cm	▪ Surface resistance x-y-direction	0.2 Ohm / square
▪ Type of liner	PE-coated paper		

Properties

- | | | | |
|-----------------------------------|-----|-----------------------------------|-----|
| ▪ Static shear resistance at 23°C | ●●● | ▪ Static shear resistance at 40°C | ●●● |
|-----------------------------------|-----|-----------------------------------|-----|

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=60233>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.